

## JUICEBOX® 40

**Residential Charging Stations** 





**JuiceBox** 

# Charge forward with the best-selling smart home charging station

JuiceBox 40, the best-selling smart home charging station, combines speed, performance and value. Enjoyed by thousands of satisfied EV drivers, it delivers all the safety and smart charging features you need to make home charging easy, reliable and cost-effective.

JuiceBox is the only line of charging stations that affords both direct user control and smart grid optimization, accessible through our software platform, JuiceNet®.

- Control charging anywhere, anytime via our mobile app and web portal
- Reduce your energy costs by scheduling charging when rates are low
- Select a cleaner electricity mix to reduce your emissions (in applicable geographies)
- Participate in smart grid programs to further lower the cost of owning and driving your
  EV (in applicable geographies)

### Why JuiceBox?

#### Up to 7x Faster Charging

Spend less time waiting for your EV to charge and more time enjoying the drive

#### Powered by JuiceNet

Monitor and schedule charging with intuitive mobile app & web portal to save time and money

#### Easy to Use and Install

Small, lightweight enclosure; lockable, quick-release mount; weatherproof for indeer/outdoor installation

#### **Universal Compatibility**

SAE-J1772<sup>™</sup> plug ensures compatibility with all EVs\*

#### **Cleaner Driving**

Optimize charging times and participate in smart grid programs to reduce emissions; ENERGY STAR®-certified<sup>†</sup>

#### **See Charger Status**

Dynamic LED lights display WiFi connectivity and charging behavior

<sup>\*</sup>Tesla requires adapter


## enel x

#### JuiceBox JuiceBox® 40 Specifications Power: 40A, 9.6 kW maximum (adjustable) 8 **Electrical Characteristics** Single phase input: nominal voltage 208/240 VAC, voltage range 177 – 264 VAC 2.3 ft (0.7 m) with NEMA 14-50 plug **Input Cable & Plug** > 2.3 ft (0.7 m) UL-rated hardwire conduit & wiring 25 ft cable **Output Cable & Connector** J1772 standard compliant > Precision measurement of power, energy, voltage & current Automatic notifications: time-of-use in effect, start of charge, end of charge, unit offline, unit back online, car needs to be plugged in to charge JuiceNet® App > Web-based portal for desktop access See JuiceNet app data sheet for more on convenient features **Smart Grid Connectivity** Built-in WiFi Connectivity (802.11 b/g/n 2.4 GHz) End-to-end AES-256-based encrypted protocols 90-day, 15-minute interval data storage **Firmware** Over-the-air (OTA) upgradeable firmware Persistent data storage upon power interruption **Emissions Reduction** > Available via optional JuiceNet Green software upgrade > Dynamic LED lights show charging status: network connectivity, charging in progress, delaying charging, standby Weatherproof, dust-tight, polycarbonate enclosure: NEMA 4X **Enclosure** Quick-release wall mounting bracket included Built-in security lock and integrated cable management Operating Temperature: -40°F to 140°F (-40°C to 60°C) Main enclosure: H: 18.5 in (469 mm) x W: 6.8 in (173 mm) x D: 5.8 in (147 mm) **Weight & Dimensions** 15 lbs (6.8 kg) FCC Part 15 Class B, NEC 625 compliant, ENERGY STAR®† **Codes & Standards** OpenADR 2.0b compliant > UL and cUL Listed Safety 3-year limited product warranty (parts only) for use under normal residential operating Warranty Made in USA > From domestic & imported parts

JUICEBOX and JUICENET are registered trademarks of Enel X North America, an Enel Group company. Other product and company names mentioned herein may be trademarks or trade names of their respective owners.

†Certification pending

2020.01.16



6.8"

