enel *** way**



Charge faster at home with the high-power JuiceBox 48

JuiceBox 48 is a smart home charging station with a high maximum power output for drivers whose cars accept higher power levels, such as many Tesla models.* The JuiceBox 48 packs 11.5 kilowatts, and automatically adjusts to an EV's accepted power level for safe, convenient home charging. JuiceBox provides easy, reliable and cost-effective charging to thousands of satisfied EV drivers and is the only line of charging stations that affords both direct user control and smart grid optimization through our software platform, JuiceNet[®].

- Charge your vehicle faster with 11.5 kW maximum power output
- · Control charging anywhere, anytime via our mobile app and web portal
- · Reduce your energy costs by scheduling charging when rates are low
- Select a cleaner electricity mix to reduce your emissions (in applicable geographies)
- Participate in smart grid programs to further lower the cost of owning and driving your EV (in applicable geographies)

Why JuiceBox?

Up to 8x Faster Charging

Spend less time waiting for your EV to charge and more time enjoying the drive

Universal Compatibility

SAE-J1772[™] plug ensures compatibility with all EVs*

Powered by JuiceNet

Monitor and schedule charging with intuitive mobile app and web portal to save time and money

Cleaner Driving

Optimize charging times and participate in smart grid programs to reduce emissions; ENERGY STAR®-certified[†]

Easy to Use and Install

Small, lightweight enclosure; lockable, quick-release mount; weatherproof for indoor/outdoor installation

JuiceBox

Charge Anywhere

With the JuicePass App, charge at home, or on the go!

enel

	6.8 in/17.3 cm	
JuiceBox 48 Specific	JuiceBox	energy
	> Safety Rated: 48A Max	NERGY STAR
	> Single phase input: nominal voltage	(II)
Electrical Characteristics	> Single phase input: nominal voltage 110-240 VAC ~60 Hz	
	> Power: 5.3 kW at 110 VAC, 11.5 kW	
	at 240 VAC	-
Input Cable	> 2.5 ft/0.8 m hardwire pigtail	
Output Cable &	> 25 ft/7.6 m cable	
Connector	> J1772 standard compliant	
JuicePass [®] App	Precision measurement of power, energy, voltage & current	
	> Automated notifications: time-of-use in effect, start of charge, end of charge,	
	unit offline, unit back online, car not plugged in by a set time	
	> Web-based portal for desktop access	
	> See JuicePass App Data Sheet for more information on convenient features	
Smart Grid Connectivity	> Built-in WiFi connectivity (802.11 b/g/n 2.4 GHz)	
Firmware	> End-to-end AES-256-based encrypted protocols	
	> 90-day, 15-minute interval data storage	
	> Over-the-air (OTA) upgradeable firmware	
	> Persistent data storage upon power interruption	
Emissions Reduction	> Available via optional JuiceNet Green software upgrade	
Enclosure	> Dynamic LED lights show charging status: network connectivity, charging in progress,	
	delayed charging, standby, charge complete/EV not drawing power	
	> IP66: Weatherproof, dust-tight	
	IK10: Resistant polycarbonate case	
	Quick-release wall mounting bracket included	
	Built-in security lock and integrated cable management	
	Operating Temperature: -40°F to 140°F (-40°C to 60°C)	
Weight & Dimensions	Main enclosure: H: 18.5 in/469 mm x W: 6.8 in/173 mm x D: 5.8 in/147 mm	
	> 17 lbs/7.7 kg	
Codes & Standards	FCC Part 15 Class B, NEC 625 compliant, OCPP 1.6J, ENERGY STAR [®]	
	> OpenADR 2.0b compliant	
Safety	> UL and cUL Listed	
Warranty	> 3-year limited product warranty (parts only) for use under normal residential	
·	operating conditions	
Made in North America	> From domestic & imported parts	
	trademarks of Enel X North America, an Enel Group company. Other product may be trademarks or trade names of their respective owners	2022.04.26

and company names mentioned herein may be trademarks or trade names of their respective owners.

Customer Support +1-844-584-2329 Commercial Sales +1-844-885-5850 🍠 enelxwayna

f enelxwayna

in Enel X Way O enelxwayna